

SPECIFICATIONS



Range specifications:



Tyre Size (Recommended)	Xlite Part No.	Wheel Size (W x D)	Stud (qty)	Stud Hole Size (mm)	Centre Bore (mm)	Pitch Circle Diameter (PCD) (mm)	Inset (mm)	HDS (offset) (mm)	Weight (kg)	Max Load (kg)	Dual Mount	Hump	Wheel Valve
235,245 75 17.5	CVAA340M	6.75 X 17.5	6	21	202	245	122	143	14.3	2500	YES	YES	70MS 07
235,245 75 17.5	CVAA340P2	6.75 X 17.5	6	21	202	245	122	143	14.3	2500	YES	YES	70MS 07
235,245 75 17.5	CVAA339M	6.75 X 17.5	6	24	202	245	122	143	14.3	2500	YES	YES	70MS 07
235,245 75 17.5	CVAA339P2	6.75 X 17.5	6	24	202	245	122	143	14.3	2500	YES	YES	70MS 07
235,245 75 17.5	CVAA284M	6.75 X 17.5	6	26	202	245	122	143	14.2	2500	YES	YES	70MS 07
235,245 75 17.5	CVAA284P2	6.75 X 17.5	6	26	202	245	122	143	14.2	2500	YES	YES	70MS 07
235,245 75 17.5	CVAA067M	6.75 X 17.5	8	24	221	275	118	141	13.3	2725	YES	NO	TR543
235,245 75 17.5	CVAA067P2	6.75 X 17.5	8	24	221	275	118	141	13.3	2725	YES	NO	TR543
235,245 75 17.5	CVAA262M	6.75 X 17.5	8	30	221	275	118	141	13.1	2725	YES	NO	TR543
235,245 75 17.5	CVAA262P2	6.75 X 17.5	8	30	221	275	118	141	13.1	2725	YES	NO	TR543
235,245 75 17.5	CVAA274M	6.75 X 17.5	10	26	176	225	121	141	14.4	3000	YES	YES	70MS 07
235,245 75 17.5	CVAA274P2	6.75 X 17.5	10	26	176	225	121	141	14.4	3000	YES	YES	70MS 07
235,245 75 17.5	CVAA344M	6.75 X 17.5	10	32	176	225	121	141	14.2	3000	YES	YES	70MS 07
235,245 75 17.5	CVAA344P2	6.75 X 17.5	10	32	176	225	121	141	14.2	3000	YES	YES	70MS 07
245,265 70 19.5	CVAA300M	7.50 X 19.5	8	26	221	275	135	155	18.2	3040	YES	YES	1670
245,265 70 19.5	CVAA300P2	7.50 X 19.5	8	26	221	275	135	155	18.2	3040	YES	YES	1670
245,265 70 19.5	CVAA301M	7.50 X 19.5	8	30	221	275	135	155	18.2	3040	YES	YES	1670
245,265 70 19.5	CVAA301P2	7.50 X 19.5	8	30	221	275	135	155	18.2	3040	YES	YES	1670
245,265 70 19.5	CVAA302M	7.50 X 19.5	8	32	221	275	135	155	18.2	3040	YES	YES	1670
245,265 70 19.5	CVAA302P2	7.50 X 19.5	8	32	221	275	135	155	18.2	3040	YES	YES	1670
255,275 70,80 22.5	CVAA203M	7.50 X 22.5	10	26	281	335	140	162	23.4	3550	YES	YES	70MS 07
255,275 70,80 22.5	CVAA203P2	7.50 X 22.5	10	26	281	335	140	162	24.4	3550	YES	YES	70MS 07
255,275 70,80 22.5	CVAA288M	7.50 X 22.5	10	32	281	335	140	162	23.3	3550	YES	YES	70MS 07
255,275 70,80 22.5	CVAA288P2	7.50 X 22.5	10	32	281	335	140	162	23.3	3550	YES	YES	70MS 07
295 60,80 22.5	CVAA121M	8.25 X 22.5	10	26	281	335	145	167	23.7	3650	YES	YES	70MS 07
295 60,80 22.5	CVAA121P2	8.25 X 22.5	10	26	281	335	145	167	23.7	3650	YES	YES	70MS 07
295 60,80 22.5	CVAA122M	8.25 X 22.5	10	32	281	335	145	167	23.5	3650	YES	YES	70MS 07
295 60,80 22.5	CVAA122P2	8.25 X 22.5	10	32	281	335	145	167	23.5	3650	YES	YES	70MS 07
315 60,70,80 22.5	CVAA046M	9.00 X 22.5	10	26	281	335	152	175	25.8	4125	YES	YES	70MS 07
315 60,70,80 22.5	CVAA046P2	9.00 X 22.5	10	26	281	335	152	175	25.8	4125	YES	YES	70MS 07
315 60,70,80 22.5	CVAA047M	9.00 X 22.5	10	32	281	335	152	175	25.6	4125	YES	YES	70MS 07
315 60,70,80 22.5	CVAA047P2	9.00 X 22.5	10	32	281	335	152	175	25.6	4125	YES	YES	70MS 07
385 55,65 22.5	CVAA003M5	11.75 X 22.5	10	26	281	335	0	0	24.4	5000	NO	NO	TR542
385 55,65 22.5	CVAA003P05	11.75 X 22.5	10	26	281	335	0	0	24.4	5000	NO	NO	TR542
385 55,65 22.5	CVAA019M5	11.75 X 22.5	10	32	281	335	0	0	24.2	5000	NO	NO	TR542
385 55,65 22.5	CVAA019PO	11.75 X 22.5	10	32	281	335	0	0	24.2	5000	NO	NO	TR542
385 55,65 22.5	CVAA040M5	11.75 X 22.5	10	26	281	335	120	0	26.3	5000	NO	YES	TR542
385 55,65 22.5	CVAA040P05	11.75 X 22.5	10	26	281	335	120	0	26.3	5000	NO	YES	TR542
385 55,65 22.5	CYAA041M5	11.75 X 22.5	10	32	281	335	120	0	26.1	5000	NO	YES	TR542
385 55,65 22.5	CVAA041P05	11.75 X 22.5	10	32	281	335	120	0	26.1	5000	NO	YES	TR542
385 55,65 22.5	CVAA059M	11.75 X 22.5	10	26	281	335	135	0	28.9	4500	NO	YES	TR542
385 55,65 22.5	CVAA059PO	11.75 X 22.5	10	26	281	335	135	0	28.9	4500	NO	YES	TR542
385 55,65 22.5	CVAA060M	11.75 X 22.5	10	32	281	335	135	0	28.7	4500	NO	YES	TR542
385 55,65 22.5	CVAA060PO	11.75 X 22.5	10	32	281	335	135	0	28.7	4500	NO	YES	TR542
385 55,65 22.5	CVAA324M	11.75 X 22.5	10	26	281	335	45	0	24.5	5000	NO	NO	TR542
385 55,65 22.5	CVAA324PO	11.75 X 22.5	10	26	281	335	45	0	24.5	5000	NO	NO	TR542
385 55,65 22.5	CVAA350M	11.75 X 22.5	10	32	281	335	45	0	24.5	5000	NO	NO	TR542
385 55,65 22.5	CVAA350PO	11.75 X 22.5	10	32	281	335	45	0	24.5	5000	NO	NO	TR542

(M) Machined Finish, (PO) Polished Outside, (P2) Polished Both Sides.

The actual wheel weight may differ by 300gms to 500gms due to manufacturing tolerances. Information was correct at the time of going to print, however, we advise that you check with us before mounting your Xlite wheels. Errors and omissions excluded.



MWheels Ltd
(Previously MWS Distribution Ltd)
50 Leestone Road
Sharston Industrial Estate
Manchester M22 4RF

+44 (0) 161 908 1023
sales@mwheels.co.uk

WWW.MWHEELS.CO.UK

MWHEELS
EXPERTS BEHIND THE WHEEL